



中国船级社
CHINA CLASSIFICATION SOCIETY

证书编号/Certificate No.
JS24PTB00391_01

型式认可证书
CERTIFICATE OF TYPE APPROVAL

兹证明本证书所述制造厂具备按照下列标准的要求生产本证书所列产品的能力和条件。

This is to certify that the manufacturer stated in the certificate meets the requirements of the standards listed below and is available with the ability and conditions to produce the products described in the certificate.

制造厂/Manufacturer

江苏兴顺消防门业有限公司
Jiangsu Xingshun Fire Door Industry Co., Ltd.

地址/Address

泰州市姜堰区三水街道桥头工业集中区
Qiaotou Industrial Centralized Zone, Sanshui Street, Jiangyan District, Taizhou City

产品名称/Product

防火门、防火窗
Fire Door/Fire Window

附加标志/Notations

无/Nil.

认可标准/Approval Standard

1. 1974年国际海上人命安全公约及其修正案第II-2章第3、9条
Regulations 3 and 9, Chapter II-2 of International Convention for the Safety of Life at Sea, 1974, as Amended
2. IMO 2010年FTP规则附件1第3部分
IMO 2010 FTP Code Annex 1 Part 3

用于/Intended for

船舶/Ships



证书有效期至/This Certificate is valid until 2030年11月30日/ Nov. 30,2030

发证机构/Issued by 中国船级社江苏分社
CHINA CLASSIFICATION SOCIETY Jiangsu Branch

签发日期/Date 2025年12月01日
Dec. 01,2025

本证书根据中国船级社规范和相关规定签发。所有证书页为一个整体，必须同时使用。纸质证书每页均须由本社盖章方为有效，电子证书含数字签名方为有效，本证书复印件无效。任何单位和个人均不应摘录或节选本证书的部分内容。有关方对所持证书的真实性有疑问时，可以向本社检验机构咨询。本证书凡是未注明版本的规范，其（发证时）最新版本适用于本证书。
This Certificate is issued pursuant to the Rules of the Society and related regulation. All pages of the certificate are taken as a whole and are used simultaneously. No paper certificate page is valid without bearing the stamp of the Society, no electronic certificates is valid without the digital signature, and no copied form of the certificate is regarded as valid. Any part of the certificate is not to be extracted or abridged by any unit or individual in any form. Related parties who are doubted about the authenticity of the certificate may inquire of the Society or its offices. **For Rules with no version indication, their latest version (at the time of issuance of the certificate) applies to the certificate.**



Form No: T01.

联系方式/Contact Us, 见本社官方网站/See official web site of the Society (<http://www.ccs.org.cn>)

UTN:P025-04402532

产品明细/Product Description

防火门/Fire Door (M0001)

名称/Name	属性（值）/Value	单位/Unit
隔热材料/Insulation Material	详见附页/See additional pages	
耐火等级/Fire Class	详见附页/See additional pages	
门页材料/Material of Door Leaf	详见附页/See additional pages	
门页厚度/Thickness of Door Leaf	详见附页/See additional pages	
门框型式/Type of Doorframe	详见附页/See additional pages	
通孔尺寸/Clear Size	详见附页/See additional pages	
隔热材料容重/Insulation Material Density	详见附页/See additional pages	

防火窗/Fire Window (M0001)

名称/Name	属性（值）/Value	单位/Unit
隔热材料/Insulation Material	详见附页/See additional pages	
耐火等级/Fire Class	详见附页/See additional pages	
玻璃厚度/Thickness of Glass	详见附页/See additional pages	null
透光尺寸/Size of Clear Light	详见附页/See additional pages	

批准的图纸/Approved Drawings

图纸批准号/ Drawings Approval No.：详见附页/See additional pages

产品认可试验报告/ Approval Test Report

试验报告编号/ Test Report No.：详见附页/See additional pages
试验报告日期/ Test Report Date：2025-03-24
试验单位/ Laboratory: 远东防火试验中心 FAR EAST FIRE TESTING CENTRE
试验单位地址/ Test Address: 上海化工区奉贤分区楚华支路511号 No.511 Cuhua zhilu, Shanghai Chemical Industry Park Fengxian Sub-Zone,Shanghai,China

试验报告编号/ Test Report No.：XS-2005001/002
试验报告日期/ Test Report Date：2025-01-03
试验单位/ Laboratory: 江苏兴顺消防门业有限公司 Jiangsu Xingshun Fire Door Industry Co., Ltd.
试验单位地址/ Test Address: 泰州市姜堰区三水街道桥头工业集中区 Qiaotou Industrial Centralized Zone, Sanshui Street, Jiangyan District, Taizhou City

认可后的产品检验方式/ Method of Product Inspection after Approval

按规范认可后应进行产品检验的产品/The product should be inspected in term of the rules;
认可后的产品检验应由本社验船师根据本社规范规定按批准的产品检验计划进行检验，经检验合格后由本社颁发船用产品证书。
After approval, product inspection should be carried out by the Surveyor of the Society in accordance with the approved product inspection scheme, and the Marine Product Certificate will be issued by the Society upon satisfactory inspection.

认可保持条件/ Maintenance Requirements of Approval

1. 型式认可后，如果产品及其重要零部件的设计、所用材料或制造方法有所改变，且影响到产品的主要特性、特征；或产品的性能指标有所更改，且超过认可的范围，则有关图纸和文件应经检验机构审批。并在检验机构认为必要时，经本社检验人员见证有关试验和进行检查，其结果应能证实仍符合认可条件。
After type approval, if there are changes to the design, materials used or manufacturing method of the product and important components and such changes affect major characteristics and properties of the product, or property indexes of the product are changed and exceed the scope of approval, related drawings and documents are to be examined and approved by the concerned survey office. Where deemed necessary by the survey office, the surveyor to the Society will go to witness relevant tests and conduct inspection and the results should be able to demonstrate compliance with the approval conditions.
2. 工厂的质量管理体系应保持有效运行，并且与认可时一致。如果质量管理体系发生改变，应经原体系认证机构审

核并报本社批准。

The quality management system of the factory shall be ensure effective operation, and shall be the same as the situation of approval. If there are any changes to the quality management system, auditing of the original certification organization for quality management system and the society's approval shall be obtained.

3. 认可证书有效期内, 如果出现可能导致本社取消认可的情况, 工厂应及时采取有效的纠正措施。

Within the validity of the approval certificate, if cases occur that may cause the Society to withdraw the approval, the manufacturer should take corrective actions in a prompt and effective manner.

4. 在认可证书有效期内, 本社检验人员可在未经事先通知的情况下对工厂的产品制造过程进行审核, 以验证产品的生产是否符合业经本社批准的图纸和文件。工厂应予以配合。

Within the validity of the approval certificate, the surveyor to the Society may pay unannounced audit to the manufacturing process of the product in order to confirm whether it is in compliance with the drawings and documents approved by the Society. The factory should provide an active cooperation and necessary for the surveyor.

5. 如果属于获得型式认可B 模式证书, 且无需颁发船用产品证书/等效证明文件的情况, 证书获得者应接受本社每年一次的定期审核, 定期审核日为认可证书期满之日对应的每一周年日, 检查工作应在周年日的前后三个月内进行。

If belong to the situation of the product has type approval mode B certificate, and marine product certificate/equivalent document is not necessary, those who have obtained the certificate should be subject to periodical audit every year. The date of periodical audit shall be each anniversary date which corresponds to the date of expiry of the relevant certificate and the periodical audit shall be done within a time span of three months before and after the annual surveillance date.

备注/Remarks

1. 该产品与A级钢舱壁通过螺栓连接, 适用于一面壁、双面壁或三面壁。实船安装时, 应按照制造厂提供的船上安装工艺进行安装, 并确保舱壁的耐火完整性不受破坏。

The connection of the product with A class bulkheads shall be fixed with bolts and applicable for one layer bulkhead, two layer bulkhead or three layer bulkhead. When the product installation on board vessels, it shall be carried out according to the manufacturer's installation procedure, and ensure the fire integrity of bulkheads not to be damaged.

2. 带窗的防火门不得用于机舱限界面上。

The fire door with window shall not be fitted in machinery space boundaries.

3. 本社已审核了产品厂无石棉声明, 但本社的审核不免除产品厂按照合同关系向订货方保证产品无石棉的责任。

The declaration of asbestos-free submitted by manufacturer has been reviewed by the Society. However, liability of the manufacturer to guarantee the products are asbestos-free to purchaser under contract will not be exempted.

中国船级社江苏分社

CCS Jiangsu Branch

注: 本证书含有附页, 共3页

Note: The certificate is attached with additional 3 page(s)

产品明细/product description

1	产品名称/Name	防火门/ Fire door
	型号/Model	262XS201-00（A-60 级单扇防火门/A-60 SINGLE FIRE PROOF DOOR）
	耐火等级/Fire class	A-60
	通孔尺寸/Clear size	1100×2200mm
	门页构成/Composition ofdoorleaf	0.8mm 不锈钢钢板+蜂巢复合防火板+0.8mm 不锈钢钢板 0.8mm stainless steel plate+honeycomb composite fireproof board+0.8mm stainless steel plate
	门页厚度/Thickness of door leaf	40mm
	门框型式/Type of doorframe	1.2mm 不锈钢钢板/1.2mm-thick stainless steel plate+蜂巢复合防火板/honeycomb composite fireproof board
	主要组成/Principal component of material	门 框 /Door fame, 门 页 /Door leaf, 铰 链 /Hinge(不 锈 钢 /Stainlesssteel,5",3 套 /sets), 门 锁 /Lock(C1), 防 火 胶 条 /Fire ruber strip(20×15mm,10×2mm,14×16mm,13×10mm)
	隔热材料/Ansulation material	蜂巢复合防火板/honeycomb composite fireproof board(标称容量 Nominal density:196kg/m²)
	窗的透光尺寸/Clear size of window	400mm×600mm
	窗玻璃/Glass of window	厚度/Thicknes:32mm;(向火面起)8mm 钢化玻璃/Toughened glass+5mm 防火液/Fireproof liquid+6mm 钢化玻璃/Toughened glass+5mm 防火液 /Fireproof liquid+8mm 钢化玻璃/Toughened glass
	逃口的通孔尺寸/Clear size of escape	420mm×520mm×40mm
	逃口构成/Composition of escape	0.8mm 钢板/Steel plate
	消防孔的通孔尺寸/Clear size of hose port	150mm×150mm×40mm
	消防孔构成/Composition of hose port	0.8mm 钢板/Steel plate
	试验报告编号/Test Report No	FT25078(报告日期/Date:2025-3-24)
	图纸批准号/Approval No.of drawings	NP25PPP01288
2	与舱壁连接方式/Connect with bulkhead	螺栓连接/By bolted
	产品名称/Name	防火门/ Fire door
	型号/Model	262XS203-00（B-15 级单扇防火门/B-15 SINGLE FIRE PROOF DOOR）
	耐火等级/Fire class	B-15
	通孔尺寸/Clear size	1200×2300mm
	门页构成/Composition ofdoorleaf	0.8mm 不锈钢钢板+35mm 蜂巢复合防火板+0.8mm 不锈钢钢板 0.8mm-thick stainless steel plate+35mm-thick honeycomb composite fireproof board+0.8mm-thick stainless steel plate
	门页厚度/Thickness of door leaf	38mm

	门框型式/Type of doorframe	1.2mm 不锈钢钢板/1.2mm-thick stainless steel plate+蜂巢复合防火板/honeycomb composite fireproof board
	主要组成/Principal component of material	门框/Door fame,门页/Door leaf,铰链/Hinge(不锈钢/Stainlesssteel,5",3 套/sets),门锁/Lock(C1),防火胶条/Fire ruber strip(10×2mm,13×10mm)
	隔热材料/Ansulation material	蜂巢复合防火板/honeycomb composite fireproof board(标称容量 Nominal density:196kg/m²)
	窗的透光尺寸/Clear size of window	400mm×600mm
	窗玻璃/Glass of window	厚度/Thicknes:17mm;(向火面起)6mm 钢化玻璃/Toughened glass+5mm 防火液/Fireproof liquid+6mm 钢化玻璃/Toughened glass
	逃口风栅的通孔尺寸/Clear size of escape& vent louver	423mm×523mm×40mm
	逃口风栅构成/Composition of escape& vent louver	0.8mm 钢板/Steel plate
	试验报告编号/Test Report No	FT25077(报告日期/Date:2025-3-7)
	图纸批准号/Approval No.of drawings	NP25PPP01288
	与舱壁连接方式/Connect with bulkhead	螺栓连接/By bolted
3	产品名称/Name	防火门/ Fire door
	型号/Model	261XS102-00 (A-60 钢质快开闭风雨密水密防火门/A-60 CLASS STEEL QUICK OPENING AND CLOSING WEATHERTIGHT FIREPROOF DOOR)
	耐火等级/Fire class	A-60
	通孔尺寸/Clear size	1200×2300mm
	门页构成/Composition ofdoorleaf	1.2mm 厚的不锈钢板+8mm 厚的无机防火芯板+空气层+38mm 厚的蜂巢复合防火板+6mm 厚的不锈钢板 1.2mm stainless steelplate + 8mm inorganic fireproof core board + air layer +38mm honeycomb composite fireproof board +6mm steel plate.
	门页厚度/Thickness of door leaf	88.2mm
	门框型式/Type of doorframe	L100×63×8mm 角钢/Angles
	主要组成/Principal component of material	门框/Door fame,门页/Door leaf,铰链/Hinge(不锈钢/Stainlesssteel,5",3 套/sets),胶条/Rubber strip(45×20mm),防火胶条/Fire rubber strip(20×4mm)
	隔热材料/Ansulation material	蜂巢复合防火板/honeycomb composite fireproof board(标称容量 Nominal density:196kg/m²), 防火板/Fireproof plate (标称容量/Nominal density:1000kg/ m³)
	窗的透光尺寸/Clear size of window	450mm×600mm
	窗玻璃/Glass of window	厚度/Thicknes:34mm;(向火面起)12mm 钢化玻璃/Toughened glass+5mm 防火液/Fireproof liquid+6mm 钢化玻璃/Toughened glass+5mm 防火液/Fireproof liquid+6mm 钢化玻璃/Toughened glass
	试验报告编号/Test Report No	FT25079(报告日期/Date:2025-3-17)
	图纸批准号/Approval No.of drawings	NP25PPP01288
	与舱壁连接方式/Connect with bulkhead	螺栓连接/By bolted
4	产品名称/Name	防火窗/Fire window
	型号/Model	263XS301-00 (A-60 级防火窗/A60 CLASS FIREPROOF WINDOW)

证书编号/Certificate No.:JS24PTB00391_01		附页/Additional Page	
	耐火等级/Fire class	A-60	
	透光尺寸/Size of clear light	2255mm×1425mm	
	主要组成/Principal component of material	主窗框/Main window frame, 副窗框/Assistant window frame, 压板/Press plate, 防火玻璃/fireproof glass,橡胶密封条/Rubber sealing strip (60×5mm)	
	隔热材料/Insulation material	陶瓷棉/Ceramic wool(标称容量/Nominal density:170kg/ m³), 无机防火板/Inorganic fireproof plate (标称容量/Nominal density:1000kg/ m³)	
	窗玻璃/Glass of window	厚度/Thicknes:28mm;(向火面起)6mm 钢化玻璃/Toughened glass+5mm 防火液/Fireproof liquid+6mm 钢化玻璃/Toughened glass+5mm 防火液/Fireproof liquid+6mm 钢化玻璃/Toughened glass	
	试验报告编号/Test Report No.	FT25006(报告日期/Date:2025-02-12)	
	图纸批准号/Approval No. of drawings	NP25PPP00814	
	与舱壁连接方式/Connect with bulkhead	焊接连接/By welding	
5	产品名称/Name	防火窗/Fire window	
	型号/Model	263XS302-00 (A-60 级防火舷窗/A60 CLASS FIRE-PROOF SIDE SCUTTLE)	
	耐火等级/Fire class	A-60	
	透光尺寸/Size of clear light	Φ450mm	
	主要组成/Principal component of material	主窗框/Main window frame, 副窗框/Assistant window frame, 压板/Press plate, 防火玻璃/fireproof glass,橡胶密封条/Rubber sealing strip (60×5mm)	
	隔热材料/Insulation material	陶瓷棉/Ceramic wool(标称容量/Nominal density:170kg/ m³), 无机防火板/Inorganic fireproof plate (标称容量/Nominal density:1000kg/ m³)	
	窗玻璃/Glass of window	厚度/Thicknes:44mm;(向火面起)10mm 钢化玻璃/Toughened glass+6mm 中空层/Hollow layer+6mm 钢化玻璃/Toughened glass+5mm 防火液/Fireproof liquid+6mm 钢化玻璃/Toughened glass+5mm 防火液/Fireproof liquid+6mm 钢化玻璃/Toughened glass	
	试验报告编号/Test Report No.	FT25006(报告日期/Date:2025-02-12)	
	图纸批准号/Approval No. of drawings	NP25PPP00814	
	与舱壁连接方式/Connect with bulkhead	焊接连接/By welding	